



Wheel spray

The abrasion-proof blended nitro-cellulose lacquer with especially high coating capability is resistant, permanent car wash resistant and offers long term protection against stone chips and road salt. Auto-K wheel sprays are used to beautify rims without expenditure of time and to protect them against corrosion. Especially qualified to protect aluminium rims.

Colours



crystal silver



titan silver

150 ml	033 037	
400 ml	233 037	233 045
500 ml	633 037	
9 ml	433 037	



gold



white

150 ml	033 038	
400 ml	233 038	
500 ml	633 038	633 046
9 ml		



Protection clear
lacquer

150 ml	033 053
400 ml	233 053
500 ml	633 053
9 ml	



Properties

Application:

- Painting car wheel rims

Product benefits:

- Particularly good covering properties
- Resistant to road salt, stonechips etc.
- Wear resistant
- Carwash resistant
- Free of heavy metals: no lead, cadmium, chrome

Binding agent base:

- Nitro combination paints

Spray coating:

- For 2 cross-coats: 50-60 µm

Drying times:

- Dust dry: after approx. 10 -15 min.
- Fast to handling: after 2 - 3 hours
- Dry hard: after 12 hours

Can be painted over:

- With itself: at any time
- With clear lacquer at any time

Paint structure:

- 1. Auto-K anti-corrosion primer
- 2. Auto-K filler/wash primer or Auto-K spray filler
- 3. Auto-K wheel spray

Note:

- Spray the wheel clear lacquer on the cleaned wheel
- Do not spray on surfaces coated with synthetic resins as the paint may lift.