



DATA SHEET

MERCALIN RS CLEAR COAT

Article number: 111510

Color: colorless

APPLICATION AREA

The Mercalin RS Clear Coat is a protective varnish in spray particularly adapted to last the duration of fluorescent marking.

It is designed to offer a great resistance to UV and to mechanical solicitation.

Its formulation confers an excellent adherence on all types of support (concrete, bitumen, sand, gravel, wood, herb...).

Its design allows the use at any positions.

COMPOSITION

- Binder : Acrylic and waxes
- Solvents : complex mix of aliphatic hydrocarbons and esters
- Gas free of CFC

PRODUCT TYPICAL CHARACTERISTICS

- Light solvent smell
- Quick drying : about 5 minutes at 20°C
- Colorless after drying
- Use at any positions

APPLICATION METHOD

- BEFORE each use: shake vigorously to mix the varnish.
- Use head up and head down thanks to its multidirectional valve.
- Apply Clear Coat at about 10 cm from the support
- MERCALIN RS CLEAR COAT can be used together with accessories (handle or pistol)
- **DO NOT PURGE** the spray after use (multidirectional valve)

Remark: The spray runs up to -15°C. Below this temperature the operation of spray can be hardly degraded because of a sharp drop of pressure inside the spray due to the low temperature.

STORAGE AND HANDLING

- The aerosols must be kept from 15 to 25°C and less than 60% relative humidity.
- Do not expose to a temperature up to 50°C.
- To be kept out of any source of ignition or heat and sunlight.
- As with all handling and storage operations, smoking is prohibited.
- The sprays Mercalin RS Clear Coat are stable at low temperature and run at freeze. Nevertheless, it is always recommended to stock those sprays at the ambient temperature before use.



HYGENE & SAFETY

- Formulation free of chlorinated solvents
- Formulation free of lead, cadmium and other heavy metals
- Aroma free (toluene, xylene...)
- CMR free

To consult the safety data sheet : www.quick-fds.com

PACKAGING

- Packaging in spray: 650 mL gross – 500 mL net
- The cap allows a precise marking and a high protection against a sudden triggering.
- Box of 12 sprays.

TECHNICAL WARRANTY/SHELF LIFE:

4 years from the production date