



DATA SHEET

PRODUCT:

MERCALIN MARKER work site marker, short-term marking

Extremely luminous, Slow breakdown by U.V.

Excellent adherence, High mechanical resistance

High covering capacity

Product code	111513	111516	111517	111518	111519	111520	111525
Colour	Fluo red	Fluo orange	Fluo yellow	Fluo green	Fluo blue	Fluo violet	Fluo pink

PACKAGING:

- CAN, gross volume 650 ml, net volume 500 ml.
- PROPELLANT GAS, CFC-free, preserves the ozone layer (isobutene/propane mix).

STORAGE AND HANDLING:

- The aerosols must be kept from 15 to 25°C and from 50 to 60% relative humidity.
- Do not expose to a temperature up to 50°C.
- To be kept out of any source of ignition or heat and sunlight.
- As with all handling and storage operations, **smoking is prohibited**.

COMPOSITION:

- Binder: acrylic.
- Pigments: mineral and organic, lead and cadmium-free.
- Solvents: complex mix with no chlorinated solvents and aroma free (toluene, xylene...)
- Formulation that respects for Health, Safety and Environment (no Xn harmful, no Xi irritant, no X harmful to aquatic organisms)

METHOD OF APPLICATION:

- Manually or with our application equipment
- Drying time: about 5'

RECOMMENDATIONS FOR USE:

- Multidirectional use 360°
- BEFORE use: Shake the can vigorously upside down to mix the paint thoroughly (the balls should be heard clearly).
- AFTER use: DO NOT PURGE
- Can be used on all types of background
- Can be used until -15°C

TECHNICAL WARRANTY/SHELF LIFE:

4 years from the production date

HYGIENE AND SAFETY:

- Refer to safety data sheet