

TECHNICAL DATA SHEET

EU-GB

Peter Kwasny GmbH, Heilbronner Strasse 96, 74831 Gundelsheim / Deutschland Telefon: +49 (0) 06269-95-0; Fax: +49 (0) 6269-95-80 internet: www.kwasny.de e-mail info@kwasny.de

Blend-in-thinner

Prod. No. 680 093

TECHNOLOGY

SprayMax[®]

- - High productivity
 - Easy application
 - Constant atomization pressure during the total application process
 - Finest aerosol dispersion
 - Professional paint result

PRODUCT

- Ideal product for spot repair and blend-in jobs
- Easy and time-saving application

Spray pattern like a spray gun

- Especially suited for clear over base systems and 2K topcoats
- Very good redissolving capacity
- Easy to polish
- Results seamless blend-in-areas

Combination of special resins and solvents

Basis of raw material:

VOC value:

766 g/l 306 g/aerosol

2K clear coats and 2K topcoats

FIELD OF APPLICATION

Recommended for: Spot repair and blend-in-jobs

Substrate:

Pre-Treatment:



The old paintwork within the blend-in area should thoroughly be topped off using a P 2000 – P 4000 grit sand paper



TECHNICAL DATA SHEET

PROCESSING

Protections:



Personal protection is required respirator mask type A2/P2



Protective gloves, e.g. from latex or nitrile

Spray passes



Apply several light spray passes to the edge of the blend-in-area immediately after application of the 2K clear coat or 2K topcoat to achieve a smooth transition.

Finish:



When work is finished, reverse aerosol and spray valve empty

Disposal: The emptied aerosols are suitable for household collection.

CHARACTERISTICS

Solid content: 4.8 % per weight related to active ingre	dient
---	-------

- Coverage: approx. 0.5 m²/can
- Degree of gloss: n/a
- Shelf life: 36 months / 20 °C
- Remarks For professional use only

SprayMax® is a registered trade mark of the Peter Kwasny Group.

The information contained in this paper corresponds to our present knowledge and is a guide to our products and their uses. It is not to be understood as a guarantee for certain properties of our products or of their specific applications. The warnings printed on our labels must be respected. Any industrial property rights should be observed.