

# **TECHNICAL DATA SHEET**

EU-GB

Peter Kwasny GmbH, Heilbronner Strasse 96, 74831 Gundelsheim / Deutschland Telefon: +49 (0) 06269-95-0; Fax: +49 (0) 6269-95-80 internet: <u>www.kwasny.de</u> e-mail <u>info@kwasny.de</u>

Control black

Prod. No. 680 100

SprayMax<sup>®</sup>

## TECHNOLOGY



- Wide spray dispersion (spray pattern analogue to a spray gun)
- High productivity
- Constant spray pressure until the can is completely empty
- Professional painting results

PRODUCT

- Very fine spray mist
- Extremely fast drying
- Can be wet or dry sanded after just 1 minute without clogging up the sanding paper

#### FIELD OF APPLICATION

Recommended for:	Checking all kinds of sanding work
Suitable substrates:	Cured, sanded surfaces such as e.g. filler

### PROCESSING

Protections:



Personal protection is required: respirator mask type A2/P2, protective gloves, e.g. from latex or nitrile



Clean the surface with SprayMax® silicone remover.

materials, primers, old paintwork etc.



Shake aerosol vigorously for 2 min before spraying. Spray to test.

Pre-Treatment:

Preliminary:





## TECHNICAL DATA SHEET

Spray passes

Apply one thin coat onto the surface that is to be sanded.

Drying:



Can be sanded after around 1 min

Continue:



Grind wet or dry together with the substrate.

Disposal:

Place the completely empty spray can into the recycling bin.

#### CHARACTERISTICS

- Raw material base: Special physically-drying coating resins
- Solid content: 1% in rel. to the diluted paint

VOC value: 721 g/l

- Degree of gloss: n/a
- Shelf life: 24 months

The description of the shelf life refers to an unused can being stored appropriately at a temperature of 15 to 25 °C and a relative humidity beneath 60%. Keep the can dry. It should stored and transported uprightly being protected from chemical and mechanical impacts. The safety instructions on the label and all legal regulations concerning the storage location have to be observed.

Remarks For professional use only

SprayMax® is a registered trade mark of the Peter Kwasny Group.

The information contained in this paper corresponds to our present knowledge and is a guide to our products and their uses. It is not to be understood as a guarantee for certain properties of our products or of their specific applications. The warnings printed on our labels must be respected. Any industrial property rights should be observed.