

Stålplast Spray Filler 1K

Product Description:

Stålplast Spray Filler 1K is a singlecomponent acrylic-based spray filler.

Range of Applications:

Stålplast Spray Filler 1K is intended for use on paint damage and sanding scratches etc. Use on cars, caravans, boats, and in the home etc. May also be used as a filling primer.

Technical Data:

Base material: Acrylic resin
Flash-point: -10°C
Fire class: 1
Drying time: 12-15 minutes
Shelf life: 1 year
Contents: 400 ml
Preparation: Carefully clean the surface to be coated.
Scrape away loose paint and rust. Bare metal surfaces must be treated with an anti-corrosion primer before applying the spray filler.

Directions for Use:

Mask-off adjoining surfaces. Shake the can thoroughly for about 1 minute before spraying.

Application:

Hold the spray-can upright at a distance of 25-30 cm when spraying, and move it at a steady speed. Apply the filler in even, thin layers, preferably waiting 15 minutes between coats. After spraying is finished, invert can and press in the valve until only propellant is released. This will prevent blocking. Use xylene to remove any unwanted paintsplashes. At temperatures of +20°C, the surface may be sanded with dry or wet fine sandpaper (280-320 dry) (approx. 800 wet) after 30-45 minutes. NOTE! Do not spray towards a naked flame or hot objects.

Packs:

Article number:
11110 Aerosol 6 x 400 ml.

Safety Instructions:

According to Material Safety Data Sheet.

