

Carosol Rostskyddsvax Universal

Product Description:

Hagmans Carosol Rostskyddsvax Universal is transparent and intended for use where a colourless rust-inhibitor is required. This product is suitable as a complementary addition to the fundamental rust protection of the car.

Range of Applications:

Hagmans Carosol Rostskyddsvax Universal may be used to protect machinery, equipment, tools etc. May also be used in the luggage compartment and in doorframes on cars etc.

Technical Data:

Base material: Wax
Flash-point: -10°C
Fire class: 1
Drying time: 4-6 hours
Shelf life: 1 year

Preparation:

Surfaces to be treated must be completely clean and dry. Before applying, shake the spray can well. Ensure good ventilation.

Application:

Hold the spray can at a distance of 20-40 cm. Move the can back and forth until a continuous film is obtained. This rust protection does not damage the paint, but if there are splashes on the paint they can be removed using white spirit or cold degreasing compound. After spraying is finished, invert the can and press in the valve until only propellant is released. This will prevent blocking. Normal thickness of wet layer is 50-100 µm, which corresponds to 0,5-1 dl/m². Dries to a gluey surface (e. g. on a plane sheet-metal surface) after approx. 4-6 hours.

NOTE! Do not spray towards a naked flame or hot objects.

Packs:

Article number:
11240 12 x 500 ml.

