

Carosol Tjockflytande

Rostskyddsmedel, (F40), aerosol

Product description:

Carosol Tjockflytande Rostskyddsmedel aerosol is a bitumen-based anti-corrosion treatment.

Applications:

Use Hagmans Tjockflytande Rostskyddsmedel on vehicle wheel-arches, underbody, battery terminals etc. Also suitable for use on machine parts, tools, implements etc. Ideal for use on new surfaces, as well as surfaces already undersealed areas. The product has excellent coverage and provides a mat black finish.

It creates an elastic film which provides excellent anti-corrosion protection.

Technical data:

Base: Bitumen
Flash-point: -10°C
Fire class: 1
Shelf-life: 1 year

Preparation:

Ensure that any surfaces which are to be treated have been thoroughly cleaned and are dry.

Shake the can well before application.
Ensure that the working area is well ventilated.

Directions for use:

Hold the can at a distance of 20-40 cm. Move the can backwards and forwards while spraying, until a continuous film has been achieved. This anti-corrosion product does not damage paintwork. If, however, some of the content is sprayed onto paintwork, it can be removed using thinners or cold grease remover.

Once you have finished spraying, turn the can upside down and keep the valve pressed in until only propellant is being expelled from the can. This will prevent the nozzle becoming clogged. A normal layer is 200-300 µm thick, which equals 200-300 ml/m².

The product dries to a sticky surface (e.g. on a flat sheet-metal surface) within 12-24 hours.

NB! Do not spray towards a naked flame or hot objects!

Packaging:

Article number:
11260 Aerosol can 12 x 500 ml

