

Carosol Body, white, black and grey

Product Description:

Carosol Body 500 protects against rust and stone-chips.

Range of Applications:

Carosol Body 500 is used on car sills, winged edges, front and rear panels etc., as well as for sound-dampening in, e.g., engine compartments and boots. Withstands washing with cold degreasing agents and may be over-painted with car paint.

Technical Data: (1 lit.)

Base material: Sparay Alkyd 1L
Density: 1.35 g/cm³
Flash-point: +23°C-25°C
Fire class: 2A
Shelf life: 1 year

Technical Data: (Spray container)

Flash-point: -10°C
Fire class: 1
Drying time: Approx. 15 minutes.
Shelf life: 1 year

Preparation:

Surfaces which will be rust protected and sound-damped must be dry and free of grease and dirt, and must be treated with anticorrosion primer before Carosol Body 500 is applied.

Application:

The best method of application is the Carosol spraygun (Hagmans Sprutpistol) compressed air suction directly from the 1 litre pack. Spraying may also be carried out using a cup-gun, or a pressure vessel-fed gun with a 3 mm nozzle. May also be applied with a paintbrush. Clean equipment used during application in Xylene. Must be applied only in ventilated premises.

Packs:

Article number:
11270 White 500 ml. (spray)
11280 Black 500 ml. (spray)
11290 Grey 500 ml. (spray)

11341 Grey 1 lit. (bottle)
11351 White 1 lit. (bottle)
11361 Black 1 lit. (bottle)

Safety Instructions:

According to Material Safety Data Sheet.

