

# Carosol Tunnflytande Rostskyddsmedel (TO 3)

**Product Description:**

This rust inhibitor consists of wax, bitumen and oil. As a result of its low viscosity, Carosol Tunnflytande Rostskyddsmedel (TO3) has excellent penetrating qualities in cracks, hidden pockets between sheet-metal and beams, cavities, sills etc.

**Range of Applications:**

This low-viscosity product makes an excellent primer for Hagmans Carosol Tjockflytande Rostskyddsmedel. It can also be used as an anti-corrosion agent on various machine components, tools, instruments, etc. Hagmans Carosol Tunnflytande Rostskyddsmedel has been tested and approved in accordance with Swedish Standard SIS 18 65 11.

**Technical Data:**

Base material: Wax/oil/bitumen  
Specific gravity: 0.89 g/cm<sup>3</sup>  
Flash-point: Approx. +40°C  
Fire class: 2b  
Shelf life: 1 year

**Preparation:**

Surfaces to be coated must be dry and free from dirt. Before applying, shake the can well. Ensure good ventilation.

**Application:**

Hagmans Carosol Tunnflytande Rostskyddsmedel (TO3) is applied by suction spraying directly from the 1 litre bottle or by paintbrush. This rust protection does not damage the paint, but if there are splashes on the paint they can be removed using white spirit or cold degreasing compound. Normal thickness of wet layer is 50-100 µm, which corresponds to 0,5-1 dl/m<sup>2</sup>. Dries to a gluey surface (e.g. on a plane sheet-metal surface) after approx. 4-6 hours.

**Packs:**

Article number:  
11301 1 lit.  
11303 5 lit.  
11305 20 lit.  
11308 60 lit.  
11309 200 lit.

