

# Carosol Tjockflytande Rostskyddsmedel (F40)

**Product Description:**

Hagmans Carosol Tjockflytande Rostskyddsmedel (F40) consists of wax and bitumen.

**Range of Applications:**

Hagmans Carosol Tjockflytande Rostskyddsmedel (F40) is intended for use in anti-corrosion treatment of, e.g. the underside of vehicles, in wheel-arches (wheel housing), battery poles etc. It can also be used as an anti-corrosion agent on various machine components, tools, instruments. etc. Hagmans Carosol Tjockflytande Rostskyddsmedel can also be used on surfaces, which are already treated, and have a good ability to cover and give a matt black surface. It leaves an elastic film, which provides an excellent rust protection.

**Technical Data:**

Base material: Bitumen/wax  
Specific gravity: Approx. 1,04 kg/lit.  
Flash-point: Approx. +40°C  
Fire class: 2b  
Shelf life: 1 year

**Preparation:**

Surfaces to be coated must be dry and free from dirt. Before applying, shake the can well. Ensure good ventilation.

**Application:**

Hagmans Carosol Tjockflytande Rostskyddsmedel (F40) is applied by suction spraying directly from the 1 litre bottle or by paintbrush. This rust protection does not damage the paint, but if there are splashes on the paint they can be removed using white spirit or cold degreasing compound.

Normal thickness of wet layer is 200-500 µm, which corresponds to 2-5 dl/m<sup>2</sup>. Dries to a gluey surface (e. G. on a plane sheet-metal surface) after approx. 12-24 hours.

**Packs:**

Article number:

11311	1 lit.	(can)
11312	1 lit.	(tin)
11313	5 lit.	
11315	20 lit.	
11318	60 lit.	
11319	200 lit.	

