

Hagmans Topcoat

Range of application:

Hagmans Täckfärg (topcoat) is intended for use on the car, caravan, boat, tools, equipment, etc.

Technical information:

Base material: Nitro-combination resin
Drying time at 20 °C:
Dust-dry after 10-15 min.
Non-sticky after approx. 30 min.
Thoroughly dry after approx. 24 hours

Flash-point: -10 °C
Fire class: 1
Shelf-life: 2 years
Contents: 400 ml

Preparation:

Surfaces to be treated must be completely clean. Remove any rust and grind first. Prepare the clean sheet metal surfaces using Hagmans Rostskyddsgrund (anti-corrosion base) and other surfaces with Hagmans base paint.

Directions for Use / Application:

Shake the can for at least 2 minutes after the balls begin to clatter before applying the lacquer. Test spray and check the colour. Spray a thin layer 2-3 times at a distance of approx. 25 cm; wait approx. 30-45 seconds between layers. Lacquer at normal room temperature and with good ventilation. Reverse the can after use and spray until the valve is empty.

Note: Do not spray towards open flames or hot objects.

Any splashes must be immediately removed with acetone or cellulose naphtha. Polishing is possible after 24 hours at room temperature.

Packaging:

Article number Gloss

11426 Gloss Yellow RAL 1003 400 ml
11427 Gloss Red RAL 3001 400 ml
11428 Gloss Blue RAL 5005 400 ml
11429 Gloss Green RAL 6032 400 ml
11430 Gloss White 400 ml
11480 Glossy Black RAL 9005 400 ml
11471 Orange RAL 2004 400 ml
11472 Cerise RAL 4003 400 ml
11473 Light Blue RAL 5015 400 ml
11474 Light Green RAL 6018 400 ml
11475 Light Grey RAL 7035 400 ml
11476 Brown RAL 8027 400 ml

Article number semi-gloss

11431 Semi-gloss White 400 ml
11439 Semi-gloss Black RAL 9005 400 ml

Article number Matt

11490 Matt Black RAL 9005 400 ml

Article number Metallic

11491 Gold 400 ml
11492 Silver 400 ml

Recoat with clear coat (with 11460 or 11463) is recommended.

