

Grundfärg, grey and redbrown

Product Description:

Hagmans Grundfärg is an Nc-based anti-corrosion primer.

Range of Applications:

Hagmans Grundfärg is used on sheetmetal surfaces which are then top-coated.

Technical Data:

Base material: Alkyd resin
Flash-point: -10°C
Fire class: 1
Drying time: Approx. 10 minutes
Shelf life: 1 year
Contents: 400 ml.

Preparation:

Surfaces which are to be treated must be thoroughly cleaned and free from dirt, grease, oil, rust etc. before application.

Directions for Use:

Mask-off adjoining surfaces. Shake the can well for about 1 minute after the mixing ball has been released. Ensure good ventilation.

Application:

Hold the spray-can upright at a distance of 25-30 cm when spraying, and move it at a steady speed. Spray thinly 2-3 times to avoid running, and wait approximately 30-45 seconds between each application.

After spraying is finished, invert can and press in the valve until only propellant is released.

This will prevent blocking.

Any unwanted paint must be removed immediately with white spirit.

NOTE! Do not spray towards a naked flame or hot objects.

Packs:

Article number:

11440 grey 6 x 400 ml.

11450 reddish-brown 6 x 400 ml.

Safety Instructions:

According to Material Safety Data Sheet

