

Hagmans 1-comp anti-corrosion base, red

Product description:

Hagmans 1-K Rostskyddsgrund (1-comp anti-corrosion base) is a grindable anti-corrosion primer with excellent protection against rust.

Range of application:

It is used as an anti-corrosion primer on clean sheet metal surfaces which are to be finished.

Technical information:

Base: Synthetic resin
Drying time: Approx. 10 min. 20 °C
Overcoating: For best results, after 2 hours and onwards. The product can also be wet grinding after that time with excellent results.

Shelf-life: 2 years

Net contents: 400 ml

Preparation:

Surfaces which are to be treated must be completely clean. Remove any rust and grind first.

Directions for Use:

Shake the can for at least 2 minutes after the balls begin to clatter before applying the lacquer. Test spray first. Spray a thin layer 2-3 times at a distance

of approx. 25 cm; wait about 30-45 seconds between sprayings- May be overcoated or grinded after 2 hours. Lacquer at normal room temperature and with good ventilation. Reverse the can after use and spray until the valve is empty.

Note: Do not spray towards open flames or hot objects.

Application:

Hagmans 1-K Rostskyddsgrund (1-comp anti-corrosion base) is dust dry after approx. 10 min. at + 20 °C. After approx. 2 hour of drying time, a topcoat may be applied. For extra stringent surface finishing requirements, the base paint may be grinded prior to application of the topcoat, e.g. using wet sandpaper P.600.

Remove any rust spots with fine sandpaper and wash e.g. with Hagmans Silikonborttagning (silicon removal).

Packaging:

Article number:

11444 Red Spray can 6 x 400 ml

