

Hagmans Clear lacquer, glossy

Product description:

Hagmans Klarlack (clear lacquer) is an acrylic-based fast-drying lacquer with good chemical durability and high gloss.

Range of application:

It is used as a top lacquer on metallic paint and as a protective lacquer on Hagmans Fälgfärg (rim paint). This is done to protect and preserve the tint of the paint.

Teknical information:

Base: Drying time at 20 °C: Dust-dry after Non-sticky after Thoroughly dry after Flash point: Fire class: Shelf-life: Contents:

Acrylic 10-15 min. approx. 30 min. approx. 24 hours. -10 °C 1 2 years 400 ml

Preparation:

Surfaces to be treated must be completely clean.

Directions for Use / Application:

Shake the can for at least 2 minutes after the balls begin to clatter before applying the lacquer. Spray a thin layer 2-3 time at a distance of approx. 25 cm; wait approx. 30-45 seconds between layers. Lacquer at normal room temperature and with good ventilation. Reverse the can after use and spray until the valve is empty.

Note: Do not spray towards open flames or hot objects.

Any splashes must be immediately removed using acetone or cellulose naphtha. Polishing is possible after 24 hours at room temperature.

May even be used as a clear lacquer on e.g. Carosol Body.

Packaging:

Article number: 11460 Spray can 6 x 400 ml

