

Hagmans Rim paint, silver-grey

Product description:

Hagmans Fälgfärg Silvergrå (rim paint, silver-grey) is an alkyd-based topcoat.

Teknical information:

Base material:	Alkyd resin, oil-modified (synthetic resin)
Drying time at 20°C:	
Dust dry	after 15-20 minutes
Non-sticky	after 1-2 hours
Thoroughly dry	after 6-8 days
Flash-point:	-10 °C
Fire class:	1
Shelf-life:	2 years
Contents:	400 ml

Preparation:

Surfaces which are to be treated must be thoroughly clean. Remove any rust and grind first. Prepare clean sheet metal surfaces with Hagmans Rostskyddsgrund (anti-corrosion base) and other surfaces with Hagmans Grundfärg (base paint).

Directions for Use / Application:

Shake the can for at least 2 minutes after the balls begin to clatter before applying the lacquer. Test spray and check the colour. Spray a thin layer 2-3 times at a distance of approx. 25 cm; wait approx. 30-45 seconds between layers. Recoat within 30 minutes using with the same or using Hagmans Klarlack (clear lacquer). Lacquer at normal room temperature and with good ventilation. Reverse the can after use and spray until the valve is empty. Note: Do not spray towards open flames or hot objects.

Note: Do not spray towards open flames or hot objects.

Any splashes must be immediately removed with acetone or cellulose naphtha. Polishing is possible after 24 hours at room temperature.

Packaging:

Article number:
11470 Spray can 6 x 400 ml

Colour:

Silver-grey

