



Hagmans Engine Colour Spray

TECHNICAL PRODUCT DATA SHEET

2019-06-13

Page 1/1

Hagmans Engine Colour Spray is ideal for improving the look and protection of engine parts in cars, tractors, motorcycles, etc. It can withstand up to 100-120 ° C.

Directions for Use / Application:

The surface should be clean, dry and free of rust. Primer shall not be used. Shake the can for 2 minutes after the balls began to clatter. Test spray. The colour is overcoatable with itself. Paint at normal room temperature, provide good ventilation.

NOTE! Do not spray against open fire or hot objects.

Advantages:

- Easily applied, easy to work.
- Good adhesion, high cover.
- Quick drying.
- Withstand heat up to 100-120°C.
- Free of Freon (CFC), free of lead, cadmium, chromium.

Technical information:

Adhesive: Nitro-alkyd resin.

Film thickness: After 2 intersecting layers: about 20-30 µm.

Drying time: After about 30 minutes.

Non-stick: After about 1 hour

Thoroughly dry: After about 24 hours

Contents: 400 ml

Note:

Do not spray surfaces that are previously painted with synthetic resin, as there is a risk of the paint rising.

Packaging:

Article number:

11481 Black Spray can 6 x 400 ml

11482 Red Spray can 6 x 400 ml