

Rostskyddsprimer

Product Description:

Hagmans Rostskyddsprimer is a chromate-free alkyd-based primer with rustinhibiting characteristics.

Range of Applications:

Hagmans Rostskyddsprimer is intended for use on sheet-metal surfaces which will be top-coated. Use on cars, caravans, equipment, tools etc. Gives excellent results as a primer under Carosol Body.

Technical Data:

Base material: Alkyd
Density: Approx. 1.42 g/cm³
Flash-point: +26°C
Fire class: 2a
Drying time: Approx. 30 minutes
Shelf life: 1 year

Preparation:

Surfaces to be treated must be thoroughly cleaned from dirt, grease, oil, rust etc. before application.

Directions for Use:

Stir the contents of the can until the paint is thoroughly mixed.

Application:

Spread an even layer over the surface with a paintbrush. Preferably several times. Allow to dry between each coat. Hagmans Rostskyddsprimer can also be applied by spraying with excellent results.

Coverage is 6-8 m²/litre.

After approx. 30 minutes to 3 hours or after 5 days and nights the treated surface may be over-painted with most existing paints. Xylene or Hagmans Syntetförtunning 450/2 may be used for thinning and cleaning.

Packs:

Article number:

11500	Red	6 x 250 ml.
11501	Red	6 x 1 lit.
11510	Grey	6 x 250 ml.
11511	Grey	6 x 1 lit.
11513	Grey	5 lit.

