

Sheet Metal Primer

Product description:

Hagmans Sheet Metal Primer is a water-borne, acrylate-based base paint with effective corrosion-resistant pigment.

Areas of use:

Sheet Metal Primer is used for the treatment of metal surfaces, primarily in combination with Grip on Tak/Fasad (roof/facade), Takbeläggningfärg and Aquabarr®.

Technical data:

Areas of use: Outdoors
Binding agent: Acrylic
Density: 1.2
Dryness: 36 % volume
Consumption: approx. 8 m²/L
Drying time
(20 °C, 60 % RF): Dust dry in approx. 1 Hour. Coverable after approx. 3 hours. Completely dry after a few days.
Tools: Paintbrush/Roller/Spray gun
Cleaning of tools: Water
Storage: Frost-free
Potlife: Two years

Preparation:

The foundation must be clean, dry and secure. Rust damage should be sanded down or a steel brush should be used until a bare metal surface is achieved. Wash the surface with Hagmans Tak/Fasadvätt (roof/facade wash). Newer galvanised sheet metal should be etched and then thoroughly rinsed. Any residue of chalking and oxidation (white rust) is cleaned off using Hagmans Betvätska (etchant).

Application:

Apply Sheet Metal Primer using a paintbrush, roller or spray gun. Do not paint during damp weather; maximum permitted humidity is 80% RF.

Other information:

Do not use Sheet Metal Primer on plastisol-covered surfaces. Store in a frost free location. Work tools can be cleaned with water.

Förpackningar:

24480 0,3L
24481 1L
24483 4L
24484 10L

