

Insulating paint

Product description:

Hagman's Insulating Paint is a full matt, high-coverage, alkyd-based paint with high filling capacity primarily intended as an insulating paint. It can also be used as a primer or top coat paint on most indoor surfaces. Because it contains the almost odourless solvent iso-paraffin it is ideal to use for indoor painting.

Area of use:

It can be used on surfaces such as wood panelling, concrete, gypsum- and particle boards etc. With its' top insulate effect it's particularly suitable for water-, nicotine- or smoke damaged surfaces and for insulating against knot penetration from pine and spruce. It's also suitable for repainting old paper-ceilings and glue- or lime-painted surfaces where waterborne materials can't be used.

Technical specifications:

Base material:	Alkyd-based
Density:	1,50 kg/l
Fire Class:	3
Material consumption:	4-6 m ² / lt
Storage time:	2 years
A suitable application temperature is:	Minimum +5°C.
Dust dry:	6 h
Coverable:	48 h
Dryness:	53%
Dilution/Cleaning of tools:	Naphtha

Instructions for use (including application):

Pretreatment:

The surface must be clean, firm, dry and dust-free. Wash, rinse and remove old, loose paint. Glossy, alkyd-painted surfaces should be sanded. Stir the paint well

Application:

Apply with a roller or brush (brush for knot insulation). If diluted with white spirits, it can also be applied by spraying. Apply 1 layers but

always 2 layers, with 24 hours of drying in between, on surfaces with knots.

Other information:

Carefully close the can after use and store it out of reach of children. Liquid paint residues should be submitted to local environmental authorities. For more information, see Technical Data Sheet.

Packaging:

31331 - 3L
31332 - 10L

