



# Line Paint 1K

**Hagmans Linjefärg 1K** (1-comp line paint) is primarily intended for industrial and trade painting of lines.

It is an easy-to-use, durable, diffuse-open, water-borne paint with good light and gloss durability; based on polyurethane/acrylate. Extra good durability and dirt resistance can be achieved by adding a coat of lacquer to the paint, preferably Hagmans Klarlack EP-V or Klarlack 1K (1-comp).

## Technical data

Base: Polyurethane/acrylate  
 Diffusion permeable to water vapour  
 characteristics: at 2 coats, each 0.1 l/m<sup>2</sup>  
 Specific gravity: 1.2  
 Curing time: Allow approx. 3 hours curing time before next coat.  
 The floor may be brought into use after 12 hours. Full wear strength 5–7 days

Lowest surface

temperature: + 5°C

Gloss value: Approx. 40 (half gloss)

Fire hazard: No fire hazard

Material 1litre covers

consumption: approx. 10m<sup>2</sup>/ coat.

Shelf life: 2 year. Store protected from frost.

Dry content: Approx. 47 % by weight

**Preparation:** The substrate must be clean, dry and grinded matt.

**Application:** Apply with a paintbrush or roller; should be applied in two layers. Provide good ventilation. Humidity exceeding 85 % may result in a matt and streaked surface. Brushes and other equipment can be cleaned using water. Lowest surface temperature is +5°C.

**Packaging:** 1 L, 4 L

## Colours:

Closest NCS is:

Yellow: S0560-Y

Red: S1580-Y90R

White: S0500-N

