



# Golvfärg 1K Garage

## Product description:

Hagmans Golvfärg 1K Garage is a waterborne one-component floor paint based on a modified acrylate.

The product is suitable for concrete surfaces indoors and outdoors, such as garages, carports and light industry.

## TECHNICAL DATA:

Application temperature	5-25°C
Area of application	Painting of concrete floor
Base material	Acrylic
Completely dry	5-7 days
Density at 20°C	Ca 1,15
Gloss	Ca 40
Material consumption	8-10
Ready-to-use after:	12 hours (20°C)
Thinner/Cleaning	Water
Volume Solids	Ca 40%
Re-paintable	3 hours



### Pretreatment:

New concrete floors must have hardened for at least 1 week, be dry and free from dirt, oil and the like.

The cement skin must be removed by grinding, blasting or acid washing. When overpainting the existing paint, the surface must be mat-sanded and all loose paint must be removed. Untreated concrete must be primed with Hagmans Dammbindning 1K.

### Application:

With brush or a fine roller.

Should be applied in two coats. Provide good ventilation.

At humidity above 85%, a matte and flammable surface can occur.

Brushes and other equipment are cleaned in water. The lowest surface temperature is + 5 ° C.

**Garage and carport:** Let the paint dry for at least 1 week before setting up the car.

If the floor is exposed to studded tires or if you want to increase the wear resistance further should Hagmans Hjulspår garage be laid on top of the painting.