



# Wood Oil W Premium

## PRODUCT DESCRIPTION/APPLICATIONS

Hagman's Wood Oil W Premium is a water-based wood oil for finishing untreated wood or wood that has previously been finished with wood oil. The Hagman Tree Oil W Premium provides a water-repellent surface and penetrates into the wood, protecting it against drying and cracking. It can be stained.

## TECHNICAL DATA:

Applications:	Outdoors
Bonding agent:	Specially selected natural oils
Dry matter content:	22%
Density:	1.01 kg/l
Glossiness:	Dependant on surface
Cleaning/dilution:	Water
Coverage:	5–15 m <sup>2</sup> /L
Ambient temperature when applying:	Minimum +5°C
Application tools:	Brush, sponge or cloth
Dry to the touch:	2-4 hrs
Can be painted over after:	8-16 hrs
Fully dry:	Several days
Storage time:	2 years in an unopened container. To be stored away from frost.
Colour:	Clear
Flammability:	Non flammable
VOC category:	Cat. (A/f): 130 g/l (2010)

## Preparations:

The surface to be treated must be clean, dry and solid. Use a steel brush, a steel scraper or sanding paper to remove any loose, porous or decomposed wood from the surface to be treated. Clean the surface with Hagman's Wood Deck Wash and follow up with Hagman's Algae/Mold Remover on surfaces with algae or mold. Rinse thoroughly with water.



# Wood Oil W Premium

## Application:

Treat the surface with a brush, rag or sponge until the wood is saturated. Treat entire planks at a time in order to get even cover. Wipe off any excess oil after 5 to 10 minutes. Repeat the treatment if needed. Avoid applying any oil if rain is expected within 48 hrs.

## After application:

Vipe the tools carefully before cleaning them in water with some detergent. Close the lid of the tin properly before storing it away from the reach of children.