



Wood Oil Classic Premium

TECHNICAL PRODUCT DATA SHEET

2018-01-19

Page 1/2

Hagmans Wood Oil Classic Premium is a traditional wood oil intended for treatment of new, untreated wood, both impregnated or previously oiled outdoor wood. Wood Oil Classic Premium protects the substrate against dehydration and cracking, while also counteracting the growth of blue-stains, algae and mould.

TECHNICAL DATA:

Area of application:	Outdoors
Binder:	Linseed oil /alkyd
Volume Solids:	31%
Density:	0,84 kg/l
Gloss:	Dependent on surface
Thinner/Cleaning:	White spirit/naphtha
Material consumption:	4–12 m ² /L
Temperature at painting:	Minimum +5°C
Tools for painting:	Brush, sponge or cloth
Dust dry:	6 h
Re-paintable:	24 h
Completely dry:	48-72 h
Shelf life:	2 years if unopened, frost free storage
Colour:	Clear
Flammability:	Not flammable
VOC category:	(Cat. A/f): 700 g/l (2010)
Package sizes:	1L, 3L

Preparation:

The substrate must be clean, dry, and stable. Use a steel brush, scrape or grind the substrate to remove loose, porous and decomposed wood. Wash with Hagmans Deck Wash and complete with Hagmans Algae/Mould-Free on mould and fungi-infested surfaces. Rinse thoroughly with water.

Application:

Apply using a paintbrush, sponge or cloth until the wood is saturated. Wipe off any excess after 5-10 minutes. Repeat the treatment if necessary. If rain is expected within 24 hours then treatment should be avoided.



Wood Oil Classic Premium

After painting:

Wipe the tools thoroughly before cleaning in naphtha/white spirits. Close the container tightly and keep out of reach of children. N.B. Cloths drenched in oil may combust spontaneously and must therefore be burned or placed in water.