



Protäck V

Product description:

Water-borne, semi-matt and fast-drying sheet-metal paint for roofs > 15 ° inclination and facades outdoor. Used as a cover paint on new or previously painted galvanized steel and sheet-metal surfaces. (Not suitable for use on type PVF2 sheet metals. The paint has good adhesiveness and the outer layer is rain-resistant surface already after approx. 4 hours.

TECHNICAL DATA:

Binder:	Styrene acrylic/acrylic
Volume Solids:	41%
Gloss:	Semi matt
Thinner/Cleaning:	Water
Material consumption:	4–8 m ² /L.
Temperature at painting:	Minimum +5°C
Tools for painting:	Brush, roller and spray
Dust dry:	2–4 h
Re-paintable:	12 h
Completely dry:	24–48 h
Shelf life:	2 years if unopened, frost free storage
Colour:	White
Flammability:	Not flammable
VOC category:	(Cat. A/i): 140 g/l (2010)
Packaging:	1, 2, 7, 9 och 18 L

Preparation:

Wash the surfaces with Hagmans Sugar Soap outdoors or with Hagmans Roof/Facade maintenance wash. Treat oxidized, galvanized surfaces with Hagmans Stripping Compound. Rusty surfaces are cleaned by sandblasting or steel brushing by machine. The previously rusty surfaces are then primed once or twice (depending on the degree of rust) using Hagmans Sheet Metal Primer. Aluminum surfaces are scoured and primed prior to applying the paint. Before painting the surfaces must be dry, stable and thoroughly cleaned of dirt and grease and an adhesion test must be taken, according to the Gitterschnitt Method.

Protäck V



Instructions for use (including application):

Apply Pro-Cover V using a paintbrush, roller or spray gun (e.g. a Wagner PS 3.29 airless with suitable nozzle). Apply at least twice. (Minimum dryness 120 Mμ). Three coats will provide even more effective long-term protection. Avoid painting in direct sunlight or when there is risk of dew or rain.